

STV-FG25360-1 L01/50 92/8 M2 RS PAL MC 4932591



Specification		
Opening mode	Single sash + double sash	
	active	
Sash rebate height	Different special dimensions	
Handle position	1050 mm	
Lock actuation	TT/Handle-operated	
Type of faceplate	Flat faceplate	
Faceplate width	25 mm	
Faceplate variant	Variant 360-1	
Faceplate end	Angular	
Backset	50 mm	
Distance	92 mm	
Cylinder type	Profile cylinder (PZ)	
Follower	8 mm	
Follower version	Standard follower	
Auxiliary locking point type	Hook TS1 standard	
Number of auxiliary locking points	2	
DIN Direction	DIN right-hand	
Surface	Mattchrome-plated MC	
Main deadbolt	With main deadbolt	
Latch version	Standard latch	
Latch material	Zinc-steel	
Entryguard function	Without entryguard function	
Additional lock	Standard - Without additional	
	lock	
Type of fixing	Standard hardware screw	
Connection gear teeth	Present/Extendable	

Certification	
DIN 18251-3:2002-11	Class 3
Ift-certification QM 342	Class 3
SBD/PAS24	Suitable



STV-FG25360-1 L01/50 92/8 M2 RS PAL MC 4932591



STV-FG25360-1 L01/50 92/8 M2 RS PAL MC 4932591

Legend

The Winkhaus Portal

A simple click on the article number takes you directly to the article in the Winkhaus Portal. Further information such as a product description or explanations of the individual specifications are available in the Winkhaus Portal. Further information is also provided for the various profile systems, such as the sash and frame numbers. Additional documents and images for the selected product are also available in the download area.



Product base class

Explanation of abbreviations

Information in brackets is only used for individual multi-point locking systems.